





4,5kg Fire Cabinet





Features:

Made from high quality virgin LLDPE • Replaceable snap glass system for easy servicing and maintenance • Uses the same key and lock as the rest of the range • Clear moulded-in Impex windows for ease of inspection • All-around seal ensures no moisture ingress • Double-wall lid for extreme strength • Mould-in rear craters for ease of mounting • Available in a wide range of stock colours • Custom colours available on request and subject to MoQ • Heavy and wind resistant • Highly UV and temperature resistant • Sandblasted surface allows for greater friction on all outer surfaces • Also available in 9kg size

SKU	Description	↑ mm (A)	← → mm (B)	mm (C)	KG
FB-03-X	4,5kg Fire Extinguisher Cabinet	570	325	265	5,26

X = Colour options: Stock units carried in red. Other colours available on request.













contactplastic from prototype to production

FIRE EQUIPMENT

	7				Щ			ш			L			c
	15	14	13	12	11	10	9	8	7	6	5	4	3	2
2	SELF TAPPING SCREW	WASHER	RUBBER SEAL	HNDGE CAP	DOW	KEY	LOCK HINGE	LOCK RING	LOCK COMPONENT	LOCK COMPONENT	BREAK GLASS PIN	BREAK GLASS	WINDOW	LID
TOTAL WEIGHT:	COM-BO-FIR-130-Rev. 00	COM-BO-FIR-131-Rev. 00	COM-BO-FIR-146-Rev. 00	COM-AM-100-Rev. 00	COM-BO-DOW-129-Rev. 00	COM-INJ-KEY-58-Rev. 00	COM-INJ-LOC-60-Rev. 00	COM-INJ-LOC-61-Rev. 00	COM-INJ-LOC-59-Rev. 00	COM-INJ-LOC-62-Rev. 00	COM-INJ-BRE-45-Rev. 00	COM-INJ-BRE-82-Rev. 00	COM-ROTO-WIN-55-Rev. 00	COM-ROTO-FIR-52-Rev. 00
5.26 KG 4	0.0057	0.00055	0.046	0.000441	0.025522	0.006437	0.008583	0.001399	0.002226	0.006301	0.000478	0.022	0.026	1.4
+	2	2	1	4	2	2	2	2	2	2	2	1	1	2
56	contactplastic			DRAWING	Dept. Technical reference					((B)	(5)		(0)
6 7	DRAWING DRAWING DOCUMENT STANDARD DOCU			Johnathan Roth 2021/12/09	Created by				,				✓ ✓ ✓ ✓	
00 2021/12/09 1/1	AS-45F-0-Rev. 00	DWG No.	APPROVED	_	Approved by					((5)	<i>S</i>	•	/
	-							Ш			1			C



